


**Series Name:** Mol / Track Spotlight

**Project name:**

**Model No:** MML40130L


**Location:**




## Specification

|                         |                                                           |
|-------------------------|-----------------------------------------------------------|
| <b>LED Source</b>       | : LED COB                                                 |
| <b>CCT</b>              | : 2700K/3000K/3500K/4000K                                 |
| <b>CRI</b>              | : Ra 95                                                   |
| <b>SDCM</b>             | : $\leq 2$                                                |
| <b>Life Span</b>        | : >50000h-L90/B10                                         |
| <b>Wattage</b>          | : 30W                                                     |
| <b>Beam</b>             | : 12°/20°/36°/55°                                         |
| <b>Input Voltage</b>    | : 220-240V ~ 50/60Hz                                      |
| <b>Dimming Option</b>   | : Built-in knob dimming (dimming range 0-100%)            |
| <b>Installation</b>     | : 5-line 3-circuit track                                  |
| <b>Adjustment Range</b> | : Horizontal 0° ~ 360°, Vertical 0° ~ 90°                 |
| <b>Material</b>         | : High-purity die-cast aluminum lamp body                 |
| <b>Finish and Color</b> | : Anti-corrosion electrostatic spraying; Matt black/white |
| <b>IP Rating</b>        | : IP20                                                    |


12°




20°



36°



55°



## Accessories Available



**MP1-75**  
Honeycomb



**MB2-75**  
Elliptical Lens



**MP4-85**  
Barn door