

MOL

Track Spotlight








Create infinite possibilities





























Multiple optics, visual well-being, high flexibility.
3 kinds of wattage, 3 phase(5-wires) track.
Professional, designed for the museum.

















			Code	MML40109					
			Wattage	9W					
			Input Voltage	220-240V~50/60Hz					
			Installation	Track					
			Adjustable	Horizontal360°/Vertical90°					
			Weight	0.32kg					
Finish			MBK/MWT						
Remarks									
Accessories	Honeycomb Soften Lens Elliptial Lens								
Image									
Code	MP1-62		MB1-62		MB2-62				
CCT	3000K								
CRI	CRI 92								
Beam	12°		20°		36°				
Lumens	452lm		534lm		488lm				
IES									
	H(m)	E(lx)	D(m)	H(m)	E(lx)	D(m)			
	1	8133	0.20	1	4528	0.32	1	1192	0.63
	2	2033	0.39	2	1132	0.64	2	298	1.26
	3	904	0.59	3	503	0.96	3	132	1.89
	4	508	0.78	4	283	1.28	4	75	2.59
	5	325	0.98	5	181	1.60	5	48	3.15
CCT	4000K								
CRI	CRI 92								
Beam	12°		20°		36°				
Lumens	487lm		563lm		561lm				
IES									
	H(m)	E(lx)	D(m)	H(m)	E(lx)	D(m)			
	1	8707	0.20	1	4584	0.32	1	1370	0.63
	2	2177	0.39	2	1146	0.64	2	343	1.26
	3	967	0.59	3	509	0.96	3	152	1.89
	4	544	0.78	4	287	1.28	4	86	2.59
	5	348	0.98	5	183	1.60	5	55	3.15








 			Code	MML40115					
			Wattage	15W					
			Input Voltage	220-240V~50/60Hz					
			Installation	Track					
			Adjustable	Horizontal360°/Vertical90°					
			Weight	0.88kg					
			Finish	MBK/MWT					
Remarks	     								
Accessories	Honeycomb Soften Lens Elliptial Lens Anti-glare Flaps								
Image	   								
Code	MP1-MM15T MB1-MM15T MB2-MM15T MP4-0115T								
CCT	3000K								
CRI	CRI 92								
Beam	12°	20°		36°					
Lumens	957lm	1099lm		872lm					
IES									
	H(m)	E(lx)	D(m)	H(m)	E(lx)	D(m)	H(m)	E(lx)	D(m)
	1	13578	0.22	1	5157	0.42	1	2394	0.66
	2	3395	0.44	2	1289	0.84	2	599	1.32
	3	1509	0.66	3	573	1.26	3	266	1.98
	4	849	0.88	4	322	1.68	4	150	2.64
	5	543	1.10	5	206	2.10	5	96	3.30
CCT	4000K								
CRI	CRI 92								
Beam	12°	20°			36°				
Lumens	1035lm	1183lm			868lm				
IES									
	H(m)	E(lx)	D(m)	H(m)	E(lx)	D(m)	H(m)	E(lx)	D(m)
	1	13578	0.22	1	5552	0.42	1	2346	0.66
	2	3395	0.44	2	1388	0.84	2	587	1.32
	3	1509	0.66	3	617	1.26	3	261	1.98
	4	849	0.88	4	347	1.68	4	147	2.64
	5	543	1.10	5	222	2.10	5	94	3.30








 				Code	MML40124		
				Wattage	24W		
				Input Voltage	220-240V~50/60Hz		
				Installation	Track		
				Adjustable	Horizontal360°/Vertical90°		
				Weight	0.82kg		
				Finish	MBK/MWT		
Remarks							
Accessories	Honeycomb Soften Lens Elliptial Lens Anti-glare Flaps						
Image							
Code	MP1-85 MB1-85 MB2-85 MP4-85						
CCT	3000K						
CRI	CRI 92						
Beam	12°	18°	25°	36°	48°	55°	
Lumens	1406lm	1459lm	1680lm	1330lm	1483lm	1067lm	
IES	 H(m) E(lx) D(m) 1 19843 0.22 2 4961 0.44 3 2205 0.66 4 1240 0.88 5 794 1.10	 H(m) E(lx) D(m) 1 13235 0.32 2 3309 0.64 3 1471 0.96 4 827 1.28 5 529 1.60	 H(m) E(lx) D(m) 1 9370 0.42 2 2343 0.84 3 1041 1.26 4 586 1.68 5 375 2.10	 H(m) E(lx) D(m) 1 3790 0.66 2 948 1.32 3 421 1.98 4 237 2.64 5 152 3.30	 H(m) E(lx) D(m) 1 2923 0.85 2 731 1.70 3 325 2.55 4 183 3.40 5 117 4.25	 H(m) E(lx) D(m) 1 1853 1.00 2 463 2.00 3 206 3.00 4 116 4.00 5 74 5.00	
	CCT 4000K						
	CRI CRI 92						
	Beam	12°	18°	25°	36°	48°	55°
	Lumens	1587lm	1573lm	1808lm	1312lm	1576lm	1195lm
	IES	 H(m) E(lx) D(m) 1 22218 0.22 2 5555 0.44 3 2469 0.66 4 1389 0.88 5 889 1.10	 H(m) E(lx) D(m) 1 14269 0.32 2 3567 0.64 3 1585 0.96 4 892 1.28 5 571 1.60	 H(m) E(lx) D(m) 1 10083 0.42 2 2521 0.84 3 1120 1.26 4 630 1.68 5 403 2.10	 H(m) E(lx) D(m) 1 3740 0.66 2 935 1.32 3 416 1.98 4 234 2.64 5 150 3.30	 H(m) E(lx) D(m) 1 3106 0.85 2 777 1.70 3 345 2.55 4 194 3.40 5 124 4.25	 H(m) E(lx) D(m) 1 2075 1.00 2 519 2.00 3 231 3.00 4 130 4.00 5 83 5.00

 				Code	MML40136		
				Wattage	36W		
				Input Voltage	220-240V~50/60Hz		
				Installation	Track		
				Adjustable	Horizontal360°/Vertical90°		
				Weight	1.02kg		
				Finish	MBK/MWT		
Remarks	Φ82 168      						
Accessories	Honeycomb Soften Lens Elliptical Lens Anti-glare Flaps						
Image	   						
Code	MP1-85 MB1-85 MB2-85 MP4-85						
CCT	3000K						
CRI	CRI 92						
Beam	12°	18°	25°	36°	48°	55°	
Lumens	2013lm	1898lm	1099lm	1862lm	2005lm	1519lm	
IES	 H(m) E(lx) D(m) 1 25260 0.22 2 6315 0.44 3 2807 0.66 4 1579 0.88 5 1010 1.10	 H(m) E(lx) D(m) 1 16292 0.32 2 4073 0.64 3 1810 0.96 4 1018 1.28 5 652 1.60	 H(m) E(lx) D(m) 1 11438 0.42 2 2860 0.84 3 1271 1.26 4 715 1.68 5 458 2.10	 H(m) E(lx) D(m) 1 5207 0.66 2 1302 1.32 3 579 1.98 4 325 2.64 5 208 3.30	 H(m) E(lx) D(m) 1 3979 0.85 2 995 1.70 3 442 2.55 4 249 3.40 5 159 4.25	 H(m) E(lx) D(m) 1 2405 1.00 2 601 2.00 3 267 3.00 4 150 4.00 5 96 5.00	
	CCT 4000K						
	CRI CRI 92						
	Beam	12°	18°	25°	36°	48°	55°
	Lumens	2002lm	2047lm	2263lm	1854lm	2130lm	1701lm
	IES	 H(m) E(lx) D(m) 1 31808 0.22 2 7952 0.44 3 3534 0.66 4 1988 0.88 5 1272 1.10	 H(m) E(lx) D(m) 1 17570 0.32 2 4393 0.64 3 1952 0.96 4 1098 1.28 5 703 1.60	 H(m) E(lx) D(m) 1 12308 0.42 2 3077 0.84 3 1368 1.26 4 769 1.68 5 492 2.10	 H(m) E(lx) D(m) 1 5184 0.66 2 1296 1.32 3 576 1.98 4 324 2.64 5 207 3.30	 H(m) E(lx) D(m) 1 4227 0.85 2 1057 1.70 3 470 2.55 4 264 3.40 5 169 4.25	 H(m) E(lx) D(m) 1 2693 1.00 2 673 2.00 3 299 3.00 4 168 4.00 5 108 5.00

  220 278Max	Code	MML40109T																																																										
	Wattage	9W																																																										
	Input Voltage	220-240V~50/60Hz																																																										
	Installation	Track																																																										
	Adjustable	Horizontal360°/Vertical90°																																																										
	Weight	0.37kg																																																										
Finish	MBK/MWT																																																											
Remarks																																																												
Accessories	Honeycomb Soften Lens Elliptial Lens																																																											
Image	  																																																											
Code	MP1-50 MB1-50 MB2-50																																																											
CCT	3000K																																																											
CRI	CRI 92																																																											
Beam	12°-52°																																																											
Lumens	12°/ 175lm		30°/ 265lm		52°/ 373lm																																																							
IES	<table><tr><th>H(m)</th><th>E(lx)</th><th>D(m)</th></tr><tr><td>1</td><td>7116</td><td>0.14</td></tr><tr><td>2</td><td>1779</td><td>0.28</td></tr><tr><td>3</td><td>791</td><td>0.42</td></tr><tr><td>4</td><td>445</td><td>0.56</td></tr><tr><td>5</td><td>285</td><td>0.70</td></tr></table>		H(m)	E(lx)	D(m)	1	7116	0.14	2	1779	0.28	3	791	0.42	4	445	0.56	5	285	0.70	<table><tr><th>H(m)</th><th>E(lx)</th><th>D(m)</th></tr><tr><td>1</td><td>1022</td><td>0.54</td></tr><tr><td>2</td><td>256</td><td>1.08</td></tr><tr><td>3</td><td>114</td><td>1.62</td></tr><tr><td>4</td><td>64</td><td>2.16</td></tr><tr><td>5</td><td>41</td><td>2.70</td></tr></table>		H(m)	E(lx)	D(m)	1	1022	0.54	2	256	1.08	3	114	1.62	4	64	2.16	5	41	2.70	<table><tr><th>H(m)</th><th>E(lx)</th><th>D(m)</th></tr><tr><td>1</td><td>647</td><td>0.95</td></tr><tr><td>2</td><td>162</td><td>1.89</td></tr><tr><td>3</td><td>72</td><td>2.84</td></tr><tr><td>4</td><td>40</td><td>3.78</td></tr><tr><td>5</td><td>26</td><td>4.73</td></tr></table>		H(m)	E(lx)	D(m)	1	647	0.95	2	162	1.89	3	72	2.84	4	40	3.78	5	26	4.73
H(m)	E(lx)	D(m)																																																										
1	7116	0.14																																																										
2	1779	0.28																																																										
3	791	0.42																																																										
4	445	0.56																																																										
5	285	0.70																																																										
H(m)	E(lx)	D(m)																																																										
1	1022	0.54																																																										
2	256	1.08																																																										
3	114	1.62																																																										
4	64	2.16																																																										
5	41	2.70																																																										
H(m)	E(lx)	D(m)																																																										
1	647	0.95																																																										
2	162	1.89																																																										
3	72	2.84																																																										
4	40	3.78																																																										
5	26	4.73																																																										
CCT	4000K																																																											
CRI	CRI 92																																																											
Beam	12°-52°																																																											
Lumens	12°/ 175lm		30°/ 298lm		52°/ 401lm																																																							
IES	<table><tr><th>H(m)</th><th>E(lx)</th><th>D(m)</th></tr><tr><td>1</td><td>7454</td><td>0.14</td></tr><tr><td>2</td><td>1864</td><td>0.28</td></tr><tr><td>3</td><td>828</td><td>0.42</td></tr><tr><td>4</td><td>466</td><td>0.56</td></tr><tr><td>5</td><td>298</td><td>0.70</td></tr></table>		H(m)	E(lx)	D(m)	1	7454	0.14	2	1864	0.28	3	828	0.42	4	466	0.56	5	298	0.70	<table><tr><th>H(m)</th><th>E(lx)</th><th>D(m)</th></tr><tr><td>1</td><td>1136</td><td>0.54</td></tr><tr><td>2</td><td>284</td><td>1.08</td></tr><tr><td>3</td><td>126</td><td>1.62</td></tr><tr><td>4</td><td>71</td><td>2.16</td></tr><tr><td>5</td><td>45</td><td>2.70</td></tr></table>		H(m)	E(lx)	D(m)	1	1136	0.54	2	284	1.08	3	126	1.62	4	71	2.16	5	45	2.70	<table><tr><th>H(m)</th><th>E(lx)</th><th>D(m)</th></tr><tr><td>1</td><td>673</td><td>0.95</td></tr><tr><td>2</td><td>168</td><td>1.89</td></tr><tr><td>3</td><td>75</td><td>2.84</td></tr><tr><td>4</td><td>42</td><td>3.78</td></tr><tr><td>5</td><td>27</td><td>4.73</td></tr></table>		H(m)	E(lx)	D(m)	1	673	0.95	2	168	1.89	3	75	2.84	4	42	3.78	5	27	4.73
H(m)	E(lx)	D(m)																																																										
1	7454	0.14																																																										
2	1864	0.28																																																										
3	828	0.42																																																										
4	466	0.56																																																										
5	298	0.70																																																										
H(m)	E(lx)	D(m)																																																										
1	1136	0.54																																																										
2	284	1.08																																																										
3	126	1.62																																																										
4	71	2.16																																																										
5	45	2.70																																																										
H(m)	E(lx)	D(m)																																																										
1	673	0.95																																																										
2	168	1.89																																																										
3	75	2.84																																																										
4	42	3.78																																																										
5	27	4.73																																																										

 	Code	MML40115T																																																									
	Wattage	15W																																																									
	Input Voltage	220-240V~50/60Hz																																																									
	Installation	Track																																																									
	Adjustable	Horizontal360°/Vertical90°																																																									
	Weight	0.88kg																																																									
	Finish	MBK/MWT																																																									
Remarks	     																																																										
Accessories	Honeycomb Soften Lens Elliptial Lens Anti-glare Flaps																																																										
Image	   																																																										
Code	MP1-75 MB1-75 MB2-75 MP4-85																																																										
CCT	3000K																																																										
CRI	CRI 92																																																										
Beam	12°-52°																																																										
Lumens	12°/873lm		30°/941lm		52°/918lm																																																						
IES																																																											
	<table><tr><td>H(m)</td><td>E(lx)</td><td>D(m)</td></tr><tr><td>1</td><td>9893</td><td>0.24</td></tr><tr><td>2</td><td>2473</td><td>0.48</td></tr><tr><td>3</td><td>1099</td><td>0.72</td></tr><tr><td>4</td><td>618</td><td>0.96</td></tr><tr><td>5</td><td>396</td><td>1.20</td></tr></table>		H(m)	E(lx)	D(m)	1	9893	0.24	2	2473	0.48	3	1099	0.72	4	618	0.96	5	396	1.20	<table><tr><td>H(m)</td><td>E(lx)</td><td>D(m)</td></tr><tr><td>1</td><td>3752</td><td>0.53</td></tr><tr><td>2</td><td>938</td><td>1.06</td></tr><tr><td>3</td><td>417</td><td>1.59</td></tr><tr><td>4</td><td>235</td><td>2.12</td></tr><tr><td>5</td><td>150</td><td>2.65</td></tr></table>		H(m)	E(lx)	D(m)	1	3752	0.53	2	938	1.06	3	417	1.59	4	235	2.12	5	150	2.65	<table><tr><td>H(m)</td><td>E(lx)</td><td>D(m)</td></tr><tr><td>1</td><td>1307</td><td>0.99</td></tr><tr><td>2</td><td>327</td><td>1.89</td></tr><tr><td>3</td><td>145</td><td>2.97</td></tr><tr><td>4</td><td>82</td><td>3.96</td></tr><tr><td>5</td><td>52</td><td>4.95</td></tr></table>	H(m)	E(lx)	D(m)	1	1307	0.99	2	327	1.89	3	145	2.97	4	82	3.96	5	52	4.95
	H(m)	E(lx)	D(m)																																																								
	1	9893	0.24																																																								
	2	2473	0.48																																																								
	3	1099	0.72																																																								
	4	618	0.96																																																								
5	396	1.20																																																									
H(m)	E(lx)	D(m)																																																									
1	3752	0.53																																																									
2	938	1.06																																																									
3	417	1.59																																																									
4	235	2.12																																																									
5	150	2.65																																																									
H(m)	E(lx)	D(m)																																																									
1	1307	0.99																																																									
2	327	1.89																																																									
3	145	2.97																																																									
4	82	3.96																																																									
5	52	4.95																																																									
CCT	4000K																																																										
CRI	CRI 92																																																										
Beam	12°-52°																																																										
Lumens	12°/985lm		30°/1306lm		52°/1005lm																																																						
IES																																																											
	<table><tr><td>H(m)</td><td>E(lx)</td><td>D(m)</td></tr><tr><td>1</td><td>10058</td><td>0.24</td></tr><tr><td>2</td><td>2315</td><td>0.48</td></tr><tr><td>3</td><td>1118</td><td>0.72</td></tr><tr><td>4</td><td>629</td><td>0.96</td></tr><tr><td>5</td><td>402</td><td>1.20</td></tr></table>		H(m)	E(lx)	D(m)	1	10058	0.24	2	2315	0.48	3	1118	0.72	4	629	0.96	5	402	1.20	<table><tr><td>H(m)</td><td>E(lx)</td><td>D(m)</td></tr><tr><td>1</td><td>3860</td><td>0.53</td></tr><tr><td>2</td><td>965</td><td>1.06</td></tr><tr><td>3</td><td>429</td><td>1.59</td></tr><tr><td>4</td><td>241</td><td>2.12</td></tr><tr><td>5</td><td>154</td><td>2.65</td></tr></table>		H(m)	E(lx)	D(m)	1	3860	0.53	2	965	1.06	3	429	1.59	4	241	2.12	5	154	2.65	<table><tr><td>H(m)</td><td>E(lx)</td><td>D(m)</td></tr><tr><td>1</td><td>1442</td><td>0.99</td></tr><tr><td>2</td><td>361</td><td>1.98</td></tr><tr><td>3</td><td>160</td><td>2.97</td></tr><tr><td>4</td><td>90</td><td>3.96</td></tr><tr><td>5</td><td>58</td><td>4.95</td></tr></table>	H(m)	E(lx)	D(m)	1	1442	0.99	2	361	1.98	3	160	2.97	4	90	3.96	5	58	4.95
	H(m)	E(lx)	D(m)																																																								
	1	10058	0.24																																																								
	2	2315	0.48																																																								
	3	1118	0.72																																																								
	4	629	0.96																																																								
5	402	1.20																																																									
H(m)	E(lx)	D(m)																																																									
1	3860	0.53																																																									
2	965	1.06																																																									
3	429	1.59																																																									
4	241	2.12																																																									
5	154	2.65																																																									
H(m)	E(lx)	D(m)																																																									
1	1442	0.99																																																									
2	361	1.98																																																									
3	160	2.97																																																									
4	90	3.96																																																									
5	58	4.95																																																									

		Code	MML40124T																																																									
		Wattage	24W																																																									
		Input Voltage	220-240V~50/60Hz																																																									
		Installation	Track																																																									
		Adjustable	Horizontal360°/Vertical90°																																																									
		Weight	0.88kg																																																									
		Finish	MBK/MWT																																																									
Remarks																																																												
Accessories	Honeycomb Soften Lens Elliptial Lens Anti-glare Flaps																																																											
Image																																																												
Code	MP1-75		MB1-75		MP4-85																																																							
CCT	3000K																																																											
CRI	CRI 92																																																											
Beam	12°-52°																																																											
Lumens	12°/1251lm		30°/1334lm		52°/1292lm																																																							
IES																																																												
	<table><tr><td>H(m)</td><td>E(lx)</td><td>D(m)</td></tr><tr><td>1</td><td>14178</td><td>0.24</td></tr><tr><td>2</td><td>3545</td><td>0.47</td></tr><tr><td>3</td><td>1575</td><td>0.71</td></tr><tr><td>4</td><td>886</td><td>0.94</td></tr><tr><td>5</td><td>567</td><td>1.18</td></tr></table>		H(m)	E(lx)	D(m)	1	14178	0.24	2	3545	0.47	3	1575	0.71	4	886	0.94	5	567	1.18	<table><tr><td>H(m)</td><td>E(lx)</td><td>D(m)</td></tr><tr><td>1</td><td>5320</td><td>0.53</td></tr><tr><td>2</td><td>1330</td><td>1.06</td></tr><tr><td>3</td><td>591</td><td>1.59</td></tr><tr><td>4</td><td>333</td><td>2.12</td></tr><tr><td>5</td><td>213</td><td>2.65</td></tr></table>		H(m)	E(lx)	D(m)	1	5320	0.53	2	1330	1.06	3	591	1.59	4	333	2.12	5	213	2.65	<table><tr><td>H(m)</td><td>E(lx)</td><td>D(m)</td></tr><tr><td>1</td><td>1840</td><td>0.99</td></tr><tr><td>2</td><td>460</td><td>1.98</td></tr><tr><td>3</td><td>204</td><td>2.97</td></tr><tr><td>4</td><td>115</td><td>3.96</td></tr><tr><td>5</td><td>74</td><td>4.95</td></tr></table>		H(m)	E(lx)	D(m)	1	1840	0.99	2	460	1.98	3	204	2.97	4	115	3.96	5	74	4.95
	H(m)	E(lx)	D(m)																																																									
	1	14178	0.24																																																									
	2	3545	0.47																																																									
	3	1575	0.71																																																									
4	886	0.94																																																										
5	567	1.18																																																										
H(m)	E(lx)	D(m)																																																										
1	5320	0.53																																																										
2	1330	1.06																																																										
3	591	1.59																																																										
4	333	2.12																																																										
5	213	2.65																																																										
H(m)	E(lx)	D(m)																																																										
1	1840	0.99																																																										
2	460	1.98																																																										
3	204	2.97																																																										
4	115	3.96																																																										
5	74	4.95																																																										
CCT	4000K																																																											
CRI	CRI 92																																																											
Beam	12°		12°-52°																																																									
Lumens	12°/1455lm		30°/1530lm		52°/1483lm																																																							
IES																																																												
	<table><tr><td>H(m)</td><td>E(lx)</td><td>D(m)</td></tr><tr><td>1</td><td>14335</td><td>0.24</td></tr><tr><td>2</td><td>3584</td><td>0.47</td></tr><tr><td>3</td><td>1593</td><td>0.71</td></tr><tr><td>4</td><td>896</td><td>0.94</td></tr><tr><td>5</td><td>573</td><td>1.18</td></tr></table>		H(m)	E(lx)	D(m)	1	14335	0.24	2	3584	0.47	3	1593	0.71	4	896	0.94	5	573	1.18	<table><tr><td>H(m)</td><td>E(lx)</td><td>D(m)</td></tr><tr><td>1</td><td>5554</td><td>0.53</td></tr><tr><td>2</td><td>1389</td><td>1.06</td></tr><tr><td>3</td><td>617</td><td>1.59</td></tr><tr><td>4</td><td>347</td><td>2.12</td></tr><tr><td>5</td><td>222</td><td>2.65</td></tr></table>		H(m)	E(lx)	D(m)	1	5554	0.53	2	1389	1.06	3	617	1.59	4	347	2.12	5	222	2.65	<table><tr><td>H(m)</td><td>E(lx)</td><td>D(m)</td></tr><tr><td>1</td><td>2128</td><td>0.99</td></tr><tr><td>2</td><td>532</td><td>1.98</td></tr><tr><td>3</td><td>236</td><td>2.97</td></tr><tr><td>4</td><td>133</td><td>3.96</td></tr><tr><td>5</td><td>85</td><td>4.95</td></tr></table>		H(m)	E(lx)	D(m)	1	2128	0.99	2	532	1.98	3	236	2.97	4	133	3.96	5	85	4.95
	H(m)	E(lx)	D(m)																																																									
	1	14335	0.24																																																									
	2	3584	0.47																																																									
	3	1593	0.71																																																									
4	896	0.94																																																										
5	573	1.18																																																										
H(m)	E(lx)	D(m)																																																										
1	5554	0.53																																																										
2	1389	1.06																																																										
3	617	1.59																																																										
4	347	2.12																																																										
5	222	2.65																																																										
H(m)	E(lx)	D(m)																																																										
1	2128	0.99																																																										
2	532	1.98																																																										
3	236	2.97																																																										
4	133	3.96																																																										
5	85	4.95																																																										

		Code	MML40136T			
		Wattage	36W			
		Input Voltage	220-240V~50/60Hz			
		Installation	Track			
		Adjustable	Horizontal360°/Vertical90°			
		Weight	1.08kg			
		Finish	MBK/MWT			
Remarks						
Accessories	Honeycomb		Soften Lens	Elliptical Lens	Anti-glare Flaps	
Image						
Code	MP1-75		MB1-75	MB2-75	MP4-85	
CCT	3000K					
CRI	CRI 92					
Beam	12°-52°					
Lumens	12°/1988lm		30°/2149lm		52°/2096lm	
IES						
	H(m) E(lx) D(m)		H(m) E(lx) D(m)		H(m) E(lx) D(m)	
	1 21598 0.24		1 8570 0.53		1 2985 0.99	
	2 5400 0.47		2 2143 1.06		2 746 1.89	
	3 2400 0.71		3 952 1.59		3 332 2.97	
	4 1350 0.94		4 536 2.12		4 187 3.96	
	5 864 1.18		5 343 2.65		5 119 4.95	
CCT	4000K					
CRI	CRI 92					
Beam	12°-52°					
Lumens	12°/2251lm		30°/2366lm		52°/2295lm	
IES						
	H(m) E(lx) D(m)		H(m) E(lx) D(m)		H(m) E(lx) D(m)	
	1 22178 0.24		1 8588 0.53		1 3293 0.99	
	2 5545 0.47		2 2147 1.06		2 832 1.98	
	3 2464 0.71		3 954 1.59		3 366 2.97	
	4 1386 0.94		4 537 2.12		4 206 3.96	
	5 887 1.18		5 344 2.65		5 132 4.95	

